SINTERMATIC® Quality is everything…

Description:

Breather Vents have many applications: vacuum relief or pressure equalization on gear boxes, oil tanks or reservoirs. Common uses can be found on cylinders or valves to prevent dirt and foreign particles from entering ports open to the system.

Specification:

Used for: Operation Pressure: Operation Temp: Filtration: Air or Gas 1MPa/ 150 PSI Max. 0℃-150℃/ 35°F-300°F 40 microns(standard) 25 or 90microns upon request

Dimension and Structure:

Nickel plated steel thread body sintered together with bronze powder



Part No.	Thread**	HEX SW		Overall Length H
PTN0601-40	1/8″NPT	11.11mm	7/16″	11.1mm
PTN0602-40	1/4"NPT	14.29mm	9/16″	15.8mm
PTN0603-40	3/8″NPT	17.46mm	11/16″	19. Omm
PTN0604-40	1/2"NPT	22.23mm	7/8″	22.2mm
PTN0606-40	3/4"NPT	27.00mm	1 1/16"	25.4mm
PTN0608-40	1″NPT	33.00mm		33.3mm
PTN0610-40	1 1/4"NPT	42.00mm		35.7mm
PTN0612-40	1 1/2″NPT	50.00mm		38.1mm

* Use microns size as dash no. and add to part no. (i.e.PTN0610-40 is for filter range 40 microns. PTN0610-90 is for filter range 90microns.)

****** Standard thread is NPT, other thread upon request

